

View Online at <https://aerobasegroup.com/nsn/5950-00-942-2726>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.000 inches

Body Width:

4.687 inches

Body Height:

4.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Operating Voltage:

4.00 ac volts single component single secondary

Special Features:

Primary has 1 tap by applying primary voltage to tap secondary voltage will be 7.5 v rms and 30.0 amps

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

3 solder stud and 2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0