

View Online at <https://aerobasegroup.com/nsn/5950-00-942-4802>

Reliability Indicator:

Not established

Overall Length:

Between 2.625 inches and 2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group

Overall Height:

Between 3.937 inches and 4.249 inches

Overall Width:

Between 2.250 inches and 2.375 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

8.0 milliamperes ac single component 1st secondary

Winding Power Rating:

3.8 volts-amperes single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 4th secondary

Special Features:

One primary winding and five secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0