## NSN 5950-00-943-3961

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-943-3961

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group **Frequency Rating:** 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component **Body Length:** 1.812 inches **Body Width:** 0.937 inches **Body Height:** 2.750 inches Inclosure Type: Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded stud single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.138 inches single group Winding Operating Current: 2.0 amperes ac single component all secondary Winding Operating Voltage: 57.50 ac volts single component single primary and 99.70 ac volts single component single primary and 115.00 ac volts single component single primary and 120.00 ac volts single component single primary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:**

10 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

## NSN 5950-00-943-3961

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

