NSN 5950-00-943-8112

To Length:

To Width:

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-943-8112 |
|--|
| Center To Center Distance Between Mounting Facilities Parallel |
| 4.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel |
| 3.375 inches single mounting facility single center group |
| Frequency Rating: |
| 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 7.000 inches |
| Body Width: |
| 4.000 inches |
| Body Height: |
| 5.500 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Voltage: |
| 63.20 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 8 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

NSN 5950-00-943-8112

Power Transformer - Page 2 of 2



Fiig:

A058b0