

View Online at <https://aerobasegroup.com/nsn/5950-00-943-9432>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.156 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.156 inches single mounting facility single center group

**Impedance Rating In Ohms:**

150.0 single component all secondary

**Frequency Rating:**

20.0 hertz single component and 30.0 kilohertz single component

**Maximum Transformer Power Rating:**

30.0 milliwatts single component

**Primary To Secondary Turn Ratio:**

1 to 1 to 1 to 1 to 1 to 1 to 1 single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single component

**Body Length:**

1.500 inches

**Body Width:**

1.500 inches

**Body Height:**

2.000 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

2 primary single component and 4 secondary single component

**Thready Qty Per Inch (tpi):**

40 single group

**Thread Size:**

0.112 inches single group

**Special Features:**

High electrostatic shielding

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0