

View Online at <https://aerobasegroup.com/nsn/5950-00-944-2860>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.110 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.620 inches single mounting facility single center group

Frequency Rating:

320.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Body Length:

3.860 inches

Body Width:

2.520 inches

Body Height:

1.750 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 primary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

54.3 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

85.50 ac volts single component 1st secondary and 94.50 ac volts single component 1st secondary

Special Features:

1primary; 6 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0