

View Online at <https://aerobasegroup.com/nsn/5950-00-944-9571>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.250 inches

Body Width:

3.625 inches

Body Height:

4.438 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 6 secondary single component

Special Features:

Case metal material, primary windings rated 115 v and 115 v, secondary windings rated 5 v at 2 amp, 6.3 v at 600 ma, 6.3 v at 1.5 amps w/center tap, 6.3 v at 1.8 amp w/center tap, 6.3 v at 1.8 amp w/center tap, 6.3 v at 2.4 amp w/center tap, 750 v at no current rating w/center tap

Terminal Type And Quantity:

20 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0