

View Online at <https://aerobasegroup.com/nsn/5950-00-945-0649>

**Reliability Indicator:**

Not established

**Overall Length:**

4.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.562 inches single mounting facili type 4th center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.687 inches single mounting facili type 3rd center group

**Overall Height:**

0.875 inches

**Overall Width:**

2.188 inches

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component and single phase to three phase single component and three phase to three phase single component and three phase to single phase single component

**Transformer Winding Connection Type:**

Wye-delta

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Maximum Operating Temp:**

170.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.125 inches single mounting facili type 1st center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

5 3rd group

**Mounting Method:**

Threaded hole all groupings

**Winding Function And Quantity:**

2 primary single component and 6 secondary single component

**Thread Size:**

0.164 inches 4th group

**Winding Operating Current:**

84.0 milliamperes ac single component 2nd secondary

**Winding Power Rating:**

51.6 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

5.66 ac volts single component 2nd primary

**Special Features:**

2 primary windings; 6 secondary windings

**Thread Series Designator:**

Unc all groupings

**Terminal Type And Quantity:**

25 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0