

View Online at <https://aerobasegroup.com/nsn/5950-00-945-0649>

Reliability Indicator:

Not established

Overall Length:

4.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.562 inches single mounting facili type 4th center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.687 inches single mounting facili type 3rd center group

Overall Height:

0.875 inches

Overall Width:

2.188 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component and single phase to three phase single component and three phase to three phase single component and three phase to single phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

170.0 degrees celsius

Distance Between Mounting Facility Centers:

1.125 inches single mounting facili type 1st center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

5 3rd group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

2 primary single component and 6 secondary single component

Thread Size:

0.164 inches 4th group

Winding Operating Current:

84.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

51.6 volts-amperes single component 3rd secondary

Winding Operating Voltage:

5.66 ac volts single component 2nd primary

Special Features:

2 primary windings; 6 secondary windings

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

25 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0