NSN 5950-00-945-4620

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-945-4620

| view Online at https://aerobasegroup.com/nsn/5950-00-945-4620 |
|--|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Fungus resistant and humidity resistant and salt spray resistant and vibration resistant |
| Frequency Rating: |
| 400.0 hertz single component and 800.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Adjustment Device Drive Type: |
| Shaft single component |
| Body Length: |
| 4.688 inches |
| Body Outside Diameter: |
| 2.000 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing single group |
| Winding Function And Quantity: |
| 1 primary, variable autotransformer type single component |
| Thread Size: |
| 0.375 inches single group |
| Winding Operating Current: |
| 12.0 amperes ac single component single primary output |
| Winding Power Rating: |
| 60.0 volts-amperes single component single primary output |
| Adjustment Method And Quantity: |
| 1 adjustable core single component |
| Winding Operating Voltage: |
| 115.00 ac volts single component single primary input |
| Thread Series Designator: |
| Unef single group |
| Terminal Type And Quantity: |
| 3 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0