NSN 5950-00-947-2712

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-947-2712 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.800 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.500 inches single mounting facility single center group |
| Overall Height: |
| 1.450 inches |
| Overall Width: |
| 2.250 inches |
| Mounting Hole Diameter: |
| 0.169 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length: |
| 2.750 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Winding Operating Current: |
| 400.0 milliamperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 6.30 ac volts single component 1st secondary |
| Terminal Type And Quantity: |
| 14 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A058b0