NSN 5950-00-947-4689

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-947-4689

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.188 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.812 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.166 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 10.00 millihenries single component single winding |
| Frequency Rating: |
| 800.0 hertz single component |
| Body Length: |
| 1.562 inches |
| Body Width: |
| 1.190 inches |
| Body Height: |
| 1.312 inches |
| Maximum Operating Temp: |
| 125.0 degrees celsius |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 1.0 amperes dc single component single winding |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-947-4689

Reactor - Page 2 of 2



Fiig:

A058b0