

View Online at <https://aerobasegroup.com/nsn/5950-00-949-3245>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group

Frequency Rating:

70.0 hertz single component and 10.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

2.500 inches

End Application:

Los angeles class ssn (688); forrestal class cv; blue ridge class lcc-19; mine countermeasures support (mcs) class (lph-12); nimitz class cvn; supply class aoe; sturgeon class ssn (637)

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

50.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

60.00 ac volts single component single primary

Special Features:

Weapon system essential; dc resistance: priori type 0.65, secondary 0.25

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0