NSN 5950-00-949-3245

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-949-3245
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.687 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.437 inches single mounting facility single center group
Frequency Rating:
70.0 hertz single component and 10.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.312 inches
Body Width:
2.062 inches
Body Height:
2.500 inches
End Application:
Los angeles class ssn (688); forrestal class cv; blue ridge class lcc-19; mine countermeasures support (mcs) class (lph-12); nimitz class
cvn; supply class aoe; sturgeon class ssn (637)
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
50.0 milliamperes ac single component single secondary
Criticality Code Justification:
Feat
Winding Operating Voltage:
60.00 ac volts single component single primary
Special Features:
Weapon system essential; dc resistance: priori type 0.65, secondary 0.25
Thread Series Designator:
Unc single group
Terminal Type And Quantity:

N/a

7 solder stud

Shelf Life:

NSN 5950-00-949-3245

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0