## NSN 5950-00-949-4962

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-949-4962

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

Between 2.740 inches and 2.760 inches

#### **Body Width:**

Between 2.490 inches and 2.510 inches

#### **Body Height:**

Between 3.110 inches and 3.130 inches

#### **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded hole single group

#### **Winding Function And Quantity:**

1 primary, variable autotransformer type single component

#### **Thread Size:**

0.138 inches single group

## **Winding Operating Current:**

20.0 milliamperes dc single component single secondary

#### Winding Power Rating:

26.0 watts single component single primary input

## Winding Operating Voltage:

40.00 ac volts single component single primary input

## Special Features:

Secondary current rated as dc

#### **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

5 turret

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-949-4962

Power Autotransformer Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0