NSN 5950-00-950-3390

Radio Frequency Coil - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-950-3390 |
|---|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Moisture resistant and vibration resistant |
| Overall Length: |
| Between 0.240 inches and 0.260 inches |
| Inductance Rating: |
| 15.00 microhenries single component single winding |
| Coil Form Type: |
| Solid single component |
| Core Construction: |
| Powdered single component |
| Overall Diameter: |
| Between 0.090 inches and 0.100 inches |
| Maximum Operating Temp: |
| 125.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Conductor Size: |
| 0.02010 inches american wire gage single component single winding |
| Winding Operating Current: |
| 275.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 2.700 single component single winding |
| Quality Factor: |
| 47 single component single winding |
| Special Features: |
| Inductance tolerance, 10 pct |
| Terminal Type And Quantity: |
| 2 wire lead |
| Specification Data: |
| 00752-312102 manufacturers source control |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

NSN 5950-00-950-3390

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0