

View Online at <https://aerobasegroup.com/nsn/5950-00-950-8872>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.300 inches

Body Width:

1.250 inches

Body Height:

0.875 inches

Distance Between Mounting Facility Centers:

1.379 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Voltage:

80.00 ac volts single component single secondary

Test Data Document:

10001-2469782 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0