

View Online at <https://aerobasegroup.com/nsn/5950-00-953-1983>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.469 inches single mounting facility single center group

Frequency Rating:

2.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.440 inches

Body Width:

2.000 inches

Body Height:

1.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

2.0 milliamperes ac single component single secondary

Winding Operating Voltage:

3.80 ac kilovolts single component single secondary and 5.80 ac kilovolts single component single secondary and 6.00 ac kilovolts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0