

View Online at <https://aerobasegroup.com/nsn/5950-00-957-6267>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Overall Height:

5.124 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 3.812 inches and 3.938 inches

Body Width:

Between 3.250 inches and 3.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

2.25 amperes ac single component single secondary

Winding Operating Voltage:

24.70 ac volts single component single secondary and 26.00 ac volts single component single secondary and 27.30 ac volts single component single secondary

Special Features:

Secondary voltage output based on primary tap selection

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0