NSN 5950-00-962-8515

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-962-8515

| Thread Class (non-core): |
|---|
| 2a single group |
| Thread Direction (non-core): |
| Right-hand single group |
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.875 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.750 inches single mounting facility single center group |
| Overall Height: |
| 5.875 inches |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length: |
| 5.938 inches |
| Body Width: |
| 4.812 inches |
| Body Height: |
| 5.250 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Thready Qty Per Inch (tpi): |
| 24 single group |
| Thread Size: |
| 0.250 inches single group |
| Winding Operating Current: |
| 8.5 amperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 6.30 ac pounds per hour wet single component 1st secondary |
| Thread Series Designator: |

Thread Series Designator:

Uns single group

NSN 5950-00-962-8515

Power Transformer - Page 2 of 2



Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0