NSN 5950-00-963-5908

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-963-5908

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 1.437 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.062 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.562 inches single mounting facility single center group |
| Overall Width: |
| 0.906 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 8.3 volt-ampere single component |
| Body Height: |
| 1.812 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 4 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 6.3 milliamperes ac single component 4th secondary |
| Winding Power Rating: |
| 2.5 volts-amperes single component 2nd secondary |
| Winding Operating Voltage: |
| 98.00 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 14 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-963-5908

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0