NSN 5950-00-964-3590

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-964-3590

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility single center group |
| Frequency Rating: |
| 3.0 kilohertz single component |
| |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 2.500 inches |
| Body Height: |
| 1.500 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 5 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Special Features: |
| Primary center tapped primary winding to be bifilar wound |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 15 wire hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |

A058b0