

View Online at <https://aerobasegroup.com/nsn/5950-00-964-3789>

Reliability Indicator:

Not established

Overall Length:

5.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Overall Height:

3.875 inches

Overall Width:

3.875 inches

Frequency Rating:

320.0 hertz single component and 1.6 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

95.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

190.00 ac volts single component 1st secondary and 380.00 ac volts single component 1st secondary and 470.00 ac volts single component 1st secondary and 605.00 ac volts single component 1st secondary and 940.00 ac volts single component 1st secondary and 1.21 ac kilovolts single component 1st secondary and 1.40 ac kilovolts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0