NSN 5950-00-965-9296

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-965-9296

Reliability Indicator:
Not established
Turn Quantity:
4150 single component single winding
Mounting Slot Width:
0.625 inches single group
Body Length:
2.875 inches
Body Width:
2.140 inches
Body Height:
2.062 inches
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Slot single group
Deting Mathed
Rating Method:
Electrical single component single winding and winding turns single component single winding
-
Electrical single component single winding and winding turns single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: