NSN 5950-00-965-9296

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-965-9296

| Reliability Indicator: |
|---|
| Not established |
| Turn Quantity: |
| 4150 single component single winding |
| Mounting Slot Width: |
| 0.625 inches single group |
| Body Length: |
| 2.875 inches |
| Body Width: |
| 2.140 inches |
| Body Height: |
| 2.062 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 1 single group |
| Mounting Method: |
| Slot single group |
| Deting Mathed |
| Rating Method: |
| Electrical single component single winding and winding turns single component single winding |
| - |
| Electrical single component single winding and winding turns single component single winding |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: |
| Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01420 inches american wire gage single component single winding Winding Operating Current: 330.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 110.000 single component single winding Winding Operating Voltage: 36.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: |