## NSN 5950-00-966-2778

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-966-2778

| view Offiline at https://acrobasegroup.com/nsh/0350-00-300-2770                |
|--|
| Reliability Indicator:   |
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:      |
| 1.437 inches single mounting facility single center group                      |
| Center To Center Distance Between Mounting Facilities Parallel To Width:       |
| 1.437 inches single mounting facility single center group                      |
| Mounting Hole Diameter:  |
| 0.122 inches single group  |
| Frequency Rating:  |
| 400.0 hertz single component   |
| Input-output Phase Relationship:   |
| Single phase to single phase single component                                  |
| Body Length:   |
| 1.750 inches   |
| Body Width:  |
| 1.750 inches   |
| Body Height:   |
| 0.625 inches   |
| Installation For Which Designed:   |
| Indoor nonportable   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Flange single group and unthreaded hole single group                           |
| Winding Function And Quantity:   |
| 1 secondary single component   |
| Winding Operating Current:   |
| 60.0 milliamperes ac single component single secondary                         |
| Winding Operating Voltage:   |
| 175.00 ac pounds per hour with retaining chain single component single primary |
| Special Features:  |
| Primary rated but not included   |
| Terminal Type And Quantity:  |
| 2 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5950-00-966-2778

Current Transformer - Page 2 of 2



Fiig:

A058b0