

View Online at <https://aerobasegroup.com/nsn/5950-00-967-6314>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Fungus resistant

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 1.080 inches and 1.160 inches

**Body Outside Diameter:**

Between 1.340 inches and 1.420 inches

**Maximum Operating Temp:**

100.0 degrees celsius

**Distance Between Mounting Facility Centers:**

0.984 inches single mounting facility single center group and 1.016 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

9.0 milliamperes ac single component single primary

**Winding Power Rating:**

9.0 volts-amperes single component single primary

**Winding Operating Voltage:**

115.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0