

View Online at <https://aerobasegroup.com/nsn/5950-00-967-6920>

Reliability Indicator:

Not established

Overall Length:

2.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.000 inches

Body Width:

2.000 inches

Body Height:

2.620 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 2nd secondary and 1.0 amperes ac single component 2nd secondary and 5.4 amperes ac single component 2nd secondary

Winding Power Rating:

45.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

5.00 ac volts single component 2nd secondary or 10.20 ac volts single component 2nd secondary or 26.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0