NSN 5950-00-967-6927

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-967-6927

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.370 inches single mounting facility single center group Mounting Hole Diameter: 0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.370 inches single mounting facility single center group Mounting Hole Diameter: 0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.370 inches single mounting facility single center group Mounting Hole Diameter: 0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.370 inches single mounting facility single center group Mounting Hole Diameter: 0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Mounting Hole Diameter: 0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Mounting Hole Diameter: 0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
0.150 inches single group and 0.180 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Single phase to single phase single component Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Body Length: 2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
2.250 inches Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Body Width: 2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
2.210 inches Body Height: 2.500 inches Installation For Which Designed: Indoor portable
Body Height: 2.500 inches Installation For Which Designed: Indoor portable
2.500 inches Installation For Which Designed: Indoor portable
Installation For Which Designed: Indoor portable
Indoor portable
In all a sum a Turne s
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0