

View Online at <https://aerobasegroup.com/nsn/5950-00-976-4335>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.500 inches

Body Width:

3.750 inches

Body Height:

3.375 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 7 secondary single component

Winding Operating Current:

660.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

1primary winding; 7secondary windings

Terminal Type And Quantity:

18 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0