

View Online at <https://aerobasegroup.com/nsn/5950-00-977-2849>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.623 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

8.250 inches

Body Width:

3.625 inches

Body Height:

6.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Voltage:

73.00 ac volts single component 1st secondary and 97.00 ac volts single component 1st secondary and 129.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0