## NSN 5950-00-977-5808

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-977-5808

| ·····   |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 380.0 hertz single component and 420.0 hertz single component             |
| Input-output Phase Relationship:  |
| Three phase to three phase single component                               |
| Body Length:  |
| 5.500 inches  |
| Body Width:   |
| 4.500 inches  |
| Body Height:  |
| 6.750 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 20 single group   |
| Thread Size:  |
| 0.250 inches single group   |
| Winding Operating Current:  |
| 7.0 amperes ac single component single secondary                          |
| Winding Operating Voltage:  |
| 48.00 ac volts single component single secondary                          |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 1 threaded stud and 9 standoff, threaded stud                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
|   |

No

## NSN 5950-00-977-5808

Power Transformer - Page 2 of 2

**Fiig:** A058b0

