

View Online at <https://aerobasegroup.com/nsn/5950-00-978-4219>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.625 inches single mounting facility single center group

**Inductance Rating:**

2.50 millihenries single component single winding

**Frequency Rating:**

400.0 hertz single component and 2.4 kilohertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

3.438 inches

**Body Width:**

2.438 inches

**Body Height:**

3.000 inches

**Maximum Operating Temp:**

135.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Electrical single component single winding

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

1.5 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

11.500 single component single primary

**Winding Power Rating:**

52.3 volts-amperes single component single secondary

**Winding Operating Voltage:**

24.60 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0