# NSN 5950-00-980-0391

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-980-0391

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

4.016 inches single mounting facility single center group and 4.109 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.266 inches single mounting facility single center group and 3.359 inches single mounting facility single center group

#### **Overall Height:**

7.760 inches

# Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield brought out to terminal single component

#### **Body Length:**

Between 4.930 inches and 5.070 inches

#### **Body Width:**

Between 4.180 inches and 4.320 inches

#### **Body Height:**

Between 6.620 inches and 6.820 inches

# **Maximum Operating Temp:**

105.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 secondary single component and 1 primary single component

# Thready Qty Per Inch (tpi):

20 single group

# **Thread Size:**

0.250 inches single group

# **Winding Operating Current:**

2.0 amperes ac single component single secondary

# **Winding Operating Voltage:**

39.00 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

8 standoff, solder lug

# NSN 5950-00-980-0391

Power Transformer - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0