

View Online at <https://aerobasegroup.com/nsn/5950-00-980-0391>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.016 inches single mounting facility single center group and 4.109 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.266 inches single mounting facility single center group and 3.359 inches single mounting facility single center group

Overall Height:

7.760 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 4.930 inches and 5.070 inches

Body Width:

Between 4.180 inches and 4.320 inches

Body Height:

Between 6.620 inches and 6.820 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 secondary single component and 1 primary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

39.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0