

View Online at <https://aerobasegroup.com/nsn/5950-00-980-1970>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.310 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.310 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

6.875 inches

**Body Width:**

6.875 inches

**Body Height:**

6.500 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.312 inches single group

**Winding Operating Current:**

8.0 amperes ac single component single secondary

**Winding Operating Voltage:**

43.00 ac volts single component single secondary

**Thread Series Designator:**

Unef single group

**Terminal Type And Quantity:**

7 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0