Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-981-5362

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Mounting Slot Width: 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
Center To Center Distance Between Mounting Facilities Parallel To Length: 4.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Mounting Slot Width: 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage:
 4.375 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Mounting Slot Width: 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group Mounting Slot Width: 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage:
 3.000 inches single mounting facility single center group Mounting Slot Width: 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Voltage: 240.00 ac volts single component single primary input
 Mounting Slot Width: 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Method: Flange single group and slot single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 0.312 inches single group Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output 240.00 ac volts single component single primary input
Frequency Rating: 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 50.0 hertz single component and 1.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Zuo0 ac volts single component single primary input
Input-output Phase Relationship:Single phase to single phase single componentBody Length:Between 5.240 inches and 5.260 inchesBody Width:4.000 inchesBody Height:Between 4.615 inches and 4.635 inchesInclosure Type:OpenMounting Facility Quantity:4 single groupMounting Method:Flange single group and slot single groupWinding Function And Quantity:1 primary, fixed autotransformer type single componentWinding Operating Current:2.0 amperes ac single component single primary outputWinding Operating Voltage:240.00 ac volts single component single primary input
Single phase to single phase single component Body Length: Between 5.240 inches and 5.260 inches Body Width: 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Minding Operating Current: 2.0 amperes ac single component single primary output Minding Operating Voltage: 240.00 ac volts single component single primary input
Body Length:Between 5.240 inches and 5.260 inchesBody Width:4.000 inchesBody Height:Between 4.615 inches and 4.635 inchesInclosure Type:OpenMounting Facility Quantity:4 single groupMounting Method:Flange single group and slot single groupWinding Function And Quantity:1 primary, fixed autotransformer type single componentWinding Operating Current:2.0 amperes ac single component single primary outputWinding Operating Voltage:240.00 ac volts single component single primary input
Between 5.240 inches and 5.260 inchesBody Width:4.000 inchesBody Height:Between 4.615 inches and 4.635 inchesInclosure Type:OpenMounting Facility Quantity:4 single groupMounting Method:Flange single group and slot single groupWinding Function And Quantity:1 primary, fixed autotransformer type single componentWinding Operating Current:2.0 amperes ac single component single primary outputWinding Operating Voltage:240.00 ac volts single component single primary input
Body Width:4.000 inchesBody Height:Between 4.615 inches and 4.635 inchesInclosure Type:OpenMounting Facility Quantity:4 single groupMounting Method:Flange single group and slot single groupWinding Function And Quantity:1 primary, fixed autotransformer type single componentWinding Operating Current:2.0 amperes ac single component single primary outputWinding Operating Voltage:240.00 ac volts single component single primary input
 4.000 inches Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 Body Height: Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 Between 4.615 inches and 4.635 inches Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
Inclosure Type: Open Mounting Facility Quantity: 4 single group 4 single group Mounting Method: Flange single group and slot single group Flange single group and slot single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Minding Operating Current: 2.0 amperes ac single component single primary output Minding Operating Voltage: 240.00 ac volts single component single primary input
Open Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 4 single group Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 Mounting Method: Flange single group and slot single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 Flange single group and slot single group Winding Function And Quantity: primary, fixed autotransformer type single component Winding Operating Current: amperes ac single component single primary output Winding Operating Voltage: ac volts single component single primary input
 Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 primary, fixed autotransformer type single component Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 Winding Operating Current: 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
 2.0 amperes ac single component single primary output Winding Operating Voltage: 240.00 ac volts single component single primary input
Winding Operating Voltage: 240.00 ac volts single component single primary input
240.00 ac volts single component single primary input
Terminal Type And Quantity:
Terminar Type And Quantity.
3 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0