# NSN 5950-00-983-7836

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-983-7836

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.437 inches single mounting facility single center group

#### **Overall Height:**

Between 5.500 inches and 5.812 inches

#### Frequency Rating:

48.0 hertz single component and 400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

Between 3.813 inches and 3.938 inches

#### **Body Width:**

Between 3.250 inches and 3.375 inches

#### **Body Height:**

Between 5.062 inches and 5.250 inches

# Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 5 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.190 inches single group

# **Thread Series Designator:**

Unf single group

# **Terminal Type And Quantity:**

14 turret

# Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-983-7836

Power Transformer - Page 2 of 2



Fiig:

A058b0