

View Online at <https://aerobasegroup.com/nsn/5950-00-987-6945>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.938 inches

Body Width:

3.375 inches

Body Height:

0.812 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

700.0 milliamperes ac single component single secondary

Winding Operating Voltage:

105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0