NSN 5950-00-988-4273

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-988-4273

Reliability Indicator:
Not established
Overall Length:
2.025 inches
Overall Height:
1.250 inches
Overall Width:
1.250 inches
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core and brought out to terminal single component
Body Length:
1.280 inches
Body Width:
1.280 inches
Body Height:
1.680 inches
Maximum Operating Temp:
Maximum Operating Temp: 105.0 degrees celsius
105.0 degrees celsius
105.0 degrees celsius Distance Between Mounting Facility Centers:
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type:
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity:
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method:
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group
105.0 degrees celsius Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity:
Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component
Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi):
Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group
Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size:
Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group
Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current:

Unc single group

Thread Series Designator:

NSN 5950-00-988-4273

Power Transformer - Page 2 of 2



Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0