## NSN 5950-00-989-6603

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-989-6603

view Online at https://acrobasegroup.com/nsn/3330-00-303-0003
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.438 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
3.344 inches
Body Width:
3.906 inches
Body Height:
5.219 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
620.0 milliamperes ac single component single secondary
Winding Operating Voltage:
114.00 ac volts single component single secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
6 solder stud
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-00-989-6603

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0