

View Online at <https://aerobasegroup.com/nsn/5950-00-990-7423>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.531 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.250 inches

Body Width:

2.000 inches

Body Height:

2.000 inches

End Application:

Wasp class lhd, forrestal class cv, nimitz class cvn. Integrated underwater surveillance systems.

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

6.30 ac pounds per hour wet single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0