NSN 5950-00-990-7423

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-990-7423

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.688 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.531 inches single mounting facility single center group
Mounting Hole Diameter:
0.156 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.250 inches
Body Width:
2.000 inches
Body Height:
2.000 inches
End Application:
Wasp class lhd, forrestal class cv, nimitz class cvn. Integrated underwater surviellance systems.
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
3.0 milliamperes ac single component single secondary
Criticality Code Justification:
Feat
Winding Operating Voltage:
6.30 ac pounds per hour wet single component single secondary
Special Features:
Weapon system essential
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-00-990-7423

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0