

View Online at <https://aerobasegroup.com/nsn/5950-00-992-2360>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Mounting Slot Width:

0.190 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.750 inches

Body Width:

3.000 inches

Body Height:

4.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Operating Current:

2.0 amperes ac single component single primary input

Winding Operating Voltage:

25.00 ac volts single component single primary output and 50.00 ac volts single component single primary output and 75.00 ac volts single component single primary output and 100.00 ac volts single component single primary output and 105.00 ac volts single component single primary output and 110.00 ac volts single component single primary output and 115.00 ac volts single component single primary output and 120.00 ac volts single component single primary output and 125.00 ac volts single component single primary output

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0