

View Online at <https://aerobasegroup.com/nsn/5950-00-992-5202>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 3.094 inches and

Body Width:

Between 2.469 inches and 2.531 inches

Body Height:

Between 2.719 inches and 2.781 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Cubic Measure (non-core):

22.2 cubic inches

Unable To Decode:

Unable to decodeunable to decode

Winding Operating Current:

50.0 milliamperes ac single component 1st secondary500.0 milliamperes ac single component 2nd secondary2.0 amperes ac single component 3rd secondary500.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

52.00 ac pounds per hour wet single component 1st secondary6.00 ac pounds per hour wet single component 2nd secondary26.00 ac pounds per hour wet single component 3rd secondary80.00 ac pounds per hour wet single component 4th secondary126.00 ac pounds per hour wet single component single primary

Special Features:

1primary winding: 8secondary windings

Terminal Type And Quantity:

21 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0