

View Online at <https://aerobasegroup.com/nsn/5950-00-993-1733>

Reliability Indicator:

Not established

Transformer Function:

Interstage

Impedance Rating In Ohms:

95000.0 single component single secondary

Frequency Rating:

350.0 hertz single component and 7.0 kilohertz single component

Maximum Transformer Power Rating:

10.0 decibels single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

0.797 inches

Body Width:

0.781 inches

Body Height:

1.156 inches

Maximum Operating Temp:

105.0 degrees celsius

Distance Between Mounting Facility Centers:

0.844 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

3.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0