NSN 5950-00-993-1991

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-993-1991

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.188 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component and 125.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.094 inches
Body Width:
2.500 inches
Body Height:
4.000 inches
Installation For Which Designed:
Outdoor nonportable
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
• • •
Mounting Method:
Mounting Method:
Mounting Method: Flange single group and unthreaded hole single group
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included Terminal Type And Quantity:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 secondary single component Winding Operating Current: 5.0 amperes ac single component single secondary Winding Operating Voltage: 600.00 ac pounds per hour with retaining chain single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:

A058b0