

View Online at <https://aerobasegroup.com/nsn/5950-00-993-6896>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Overall Height:

3.150 inches

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.938 inches

Body Width:

1.812 inches

Body Height:

2.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

2.0 amperes dc single component single secondary

Winding Power Rating:

4.0 watts single component single secondary

Winding Operating Voltage:

9.60 ac volts single component single primary and 115.20 ac volts single component single primary and 117.60 ac volts single component single primary and 120.00 ac volts single component single primary and 122.40 ac volts single component single primary and 124.80 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 solder stud

Specification Or Standard:

Tf4rx01ea type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0