# NSN 5950-00-994-6182

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-994-6182

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

#### **Overall Height:**

5.280 inches

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

3.560 inches

#### **Body Width:**

3.060 inches

#### **Body Height:**

4.880 inches

# **Maximum Operating Temp:**

65.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# Thread Size:

0.164 inches single group

# **Winding Operating Current:**

710.0 milliamperes ac single component single secondary

# **Winding Operating Voltage:**

16.30 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

7 tab, solder lug

# NSN 5950-00-994-6182

Power Transformer - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0