NSN 5950-00-995-4733

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-995-4733

Reliability Indicator: Not established **Overall Length:** 14.125 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 9.500 inches single mounting facility single center group **Mounting Hole Diameter:** 0.340 inches single group and 0.353 inches single group Frequency Rating: 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Winding Shielding Method:** Internal shield grounded to core single component **Body Length:** 11.750 inches **Body Width:** 10.250 inches **Body Height:** 7.500 inches **Maximum Operating Temp:** 105.0 degrees celsius **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 8 single group **Mounting Method:** Flange single group and unthreaded hole single group **Winding Function And Quantity:** 3 primary single component and 1 secondary single component **Winding Operating Current:** 195.0 milliamperes ac single component single secondary and 340.0 milliamperes ac single component single secondary **Winding Operating Voltage:** 440.00 ac pounds per hour wet single component all primary **Terminal Type And Quantity:** 3 standoff, threaded stud and 6 threaded stud **Specification Or Standard:** Tf4rx02yy type

N/a

Shelf Life:

NSN 5950-00-995-4733

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0